

Gate Repair Services 0114633025 0834522015

www.qates.co.za



Applications

Alarm monitoring of gates Alarm monitoring of garage doors Alarm monitoring of shed doors Alarm monitoring of emergency exits Alarm monitoring of roller shutter doors

Features

Wireless Code-hopping Weatherproof plastic housing IP55 Battery Powered by AA batteries or 12VDC Trigger or Bypass from a valid opening 3 Minute Alarm if the gate is left open Tamper output

Certifications

EN300-220 Nov 1997 ETSI EN301-489-1:2001 IEC 60950:1999 ICASA: TA-2018/351

About

The wireless GATE ALARM unit is designed to secure gates or garage doors from intruders breaking in. Typically installed with a wide gap magnetic contact at the gate the unit will transmit out an alarm signal to a compatible Sherlo Code Hopping Receiver models which would be typically wired onto a alarm system.

Specification:

Encryption:	Code-Hopping
Range:	100m (Open air)
Frequency:	403MHz / 433MH
Voltage Range:	3VDC or 12VDC
Current draw:	+/- 1uA 10%
Dimensions(lxbxh):	124 x 80 x 30mm
Gross Weight:	210grams
Operating Temp:	-7°C to 65°C
Warranty:	24 Months

Order Codes

0.40.0040	
Gate Alarm Transmitter	GATE_ALARM
Magnet Wide gap (N/Closed)	TP-MA3955A
1 Channel Receiver 403MHz	RX1-500
4 Channel Receiver 403MHz	RX4-500

For Gate Motor and Intercom Repairs, or Quotes on New Installations Call the National Call Centre 011 463 3025 today 24 hour emergency 083 452 2015